



Oil Filter Side Cover

Installation Instructions:

1. **Remove product from packaging and inspect.**
2. **Oil filter cover plates install on the left side of the motorcycle. It may be necessary to remove charcoal canister on some models to install oil filter cover plate.**
3. **If you are installing on 08-2013 model that came with a charcoal canister you will only be using the Aluminum spacer, rubber washer, 1 inch long ss button head bolt, 1.750 long stainless steel button head and 2 nylon washers.**
4. **Spacer should be installed (08-2013 model year) on the bracket where your kick stand stops. The spacer goes against bike chassis then rubber washer and then oil filter cover plate. The rubber washer allows some cushioning between spacer and oil filter cover plate. Use loctite blue (242) on all fasteners.**
5. **If you are installing oil filter cover plate on 08-2013 models that did not come with charcoal canister you will need to use z-bracket included in hardware kit for installation. Follow step "4" and then use z-bracket to mount rear hole of oil filter cover bracket.**

Installation for 03-07 victory motorcycles -

Install oil filter cover plate on factory fastening points on chassis lower left between swing arm and engine.

It may be necessary to remove charcoal canister for oil filter cover installation.

03-07 model years you will use 1.0 inch long ss bolt, 1.5 long bolt, 2 nylon washers, and stainless steel washers. The stainless steel washers are to be used on the rear most bolt on the oil filter cover plate. The washers act as spacers between oil filter cover plate and chassis mounting point.